

LEVEL WALL-5

- **No Sanding Necessary**
- **Can Be Applied over Level 3 Drywall Finish**
- **Material Can Be Compressed By Trowel Or Broad knife To Create Veneer Quality Finish**
- **Multiple Application Techniques By Spray, Roller, Or Hand Application**
- **Material Adds Higher Durability To Standard Drywall Finish**
- **Easy Touch Up**
- **Has Ability To Cover Flaws Over Existing Wall Surfaces**
- **Can Be Applied Over Existing Texture Surfaces For Smooth Results**
- **Can Be Applied For Hand Textured Applications With Great Results**

Application

STEP 1: Prepare by covering to protect adjacent areas and substrates. Product may be used over new or previously painted surfaces. Surfaces must be dry, clean, free from dust, dirt, oil, wax, loose paint, wallpaper glue, etc. (Pre-priming is recommended over wallpaper removal surfaces and allowed to dry, to prevent residue from re-emulsifying).

Begin application by making sure product is properly mixed using a drill motor and paddle to achieve an ideal viscosity. Thinning of product is not required.

Apply product to surface as evenly as possible. Once material begins to set up, use a trowel or broad knife to completely smooth out surface by eliminating any stipple or other blemish caused from the method of initial application chosen.

TIP: A spray bottle with clean water can be mist sprayed to reactivate product workability and set time, if necessary.

Product should be allowed to dry at least 24 hours before paint, depending on weather conditions. Proper application will eliminate the need for sanding. Once application has dried, the surface should be inspected for the Level of quality and then prime and paint to specification.

STEP 2: Application Techniques Prepare by covering to protect adjacent areas and substrates. Product may be used over new or previously painted surfaces. Surfaces must be dry, clean, free from dust, dirt, oil, wax, loose pain

Spray Application: A heavy duty pump sprayer is recommended. One that is capable of spraying approx. 3,000 psi, or approx. 1 gallon per minute. A 3/8 hose is recommended. The recommended size of tip apertures range from .025 - .031, depending on flow rating and pump pressure of the spray rig. Apply product using cross-hatched passes, spraying both vertically, then horizontally. Adequate coverage should maintain a thickness of approx. 15 wet mils, however, the product could exceed approx. 30 wet mils, depending on circumstance and wall conditions. After product has been applied to the desired thickness, refer to the trowel instructions listed in Step 1.

NOTE: A texture rig or hopper gun can also be used to apply the product. Splatter on product and immediately back-roll using a 1/2 nap roller to lay down and flatten out the texture pattern to a stipple, then refer to trowel instructions listed in Step 1.

Roller Application: When using a paint roller to apply product, a 1/2 to 3/4 nap roller cover is recommended. Simply roll on product to the desired thickness and immediately use a trowel or broadknife to smooth over any stipple left by the roller before the stipple dries. Two coats may be necessary, depending on circumstances. Refer to trowel instructions listed in Step 1.

Hand Application: Being that the product has body by it's viscosity, it can also be hand applied. Apply using a Hawk & Trowel or Pan & Knife method and putty coat product over the entire surface. Once the desired thickness has been achieved and product begins to set up, go back to "sweeten up" any lap marks, ridges, etc., from the initial coating process. Refer to trowel instructions listed in Step 1.

NOTE: The product may also be used in the application of hand textures, ie., Santa Fe Finish, Santa Barbara Finish, etc., Many applicators prefer using this product due to the unique characteristics with finishing techniques.

Coverage

Level Wall 5 covers approximately 125 square feet per gallon, applied at approx. 15 wet mils. Results may vary depending on application of product and surface preparation.

Storage

Store at room temperature with container tightly sealed.

Clean Up

Wash tools with water.

Caution

Avoid contact with eyes. May cause irritation. If contact occurs, flush immediately with water and contact physician immediately. This product is not recommended for embedding tape. For interior use only. If sanding is necessary, use a dust-particulate respirator approved by NOSHA-MSHA.

Part#	Description	Size	Weight	UPC Code
12345	Level Wall-5	5 gal.	62 lbs.	0 00123 45678 9

SALES AND ORDER INFORMATION

145 West Meats Avenue · Orange, California 92865

Office: 714-279-0240 · Fax: 714-279-1043 · www.SpecializedBuildingProducts.com

SUBMITTAL APPROVALS

JOB NAME:

CONTRACTOR:

DATE:

SALES AND ORDER INFORMATION

145 West Meats Avenue · Orange, California 92865

Office: 714-279-0240 · Fax: 714-279-1043 · www.SpecializedBuildingProducts.com